Xerox[®] AltaLink[®] Multifunction Printers

Xerox[™]

B8145/B8155/B8170



AltaLink® B8100 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to **www.ConnectKey.com**.

System Specification	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Speed ¹	Up to 45 ppm	Up to 55 ppm	Up to 72 ppm	
Monthly Duty Cycle ²	Up to 200,000 pages	Up to 250,000 pages	Up to 300,000 pages	
Hard Drive/ Processor/Memory	Minimum 128 GB SSD/ Optional: 500 GB HDD/Inte	[®] Atom™ Quad Core 1.91 GHz/4 GB system memory		
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0	direct print, Wi-Fi/Wi-Fi Direct with optional Xerox® D	ual Band Wireless Kit, NFC, Bluetooth (iBeacon)	
Controller Features	Unified Address Book, Remote Control Panel, Config	uration Cloning, Fleet Orchestrator, Configuration Wat	chdog	
Copy and Print				
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 240	0 дрі		
First-Print-Out Time (as fast as)	3.8 seconds	3.2 seconds	3.0 seconds	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	4.4 seconds	3.7 seconds	3.2 seconds	
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6			
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, One Drive and Google Drive), Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Long Sheet (Banner) Printing, Print Around, Print on Alternate Paper; Optional: Print from and Scan to Xerox® DocuShare® Go content management			
Mobile and Cloud Ready				
Mobile Connectivity	Near-Field Communication (NFC); Optional: Wi-Fi D	irect, Wi-Fi (802.11 b/g/n/αc), AirPrint (iOS) including	iBeacon (Bluetooth)	
Mobile Printing	AirPrint®, Mopria®, Xerox® Print Service (Android), @	PrintByXerox App; Optional: Xerox® Workplace Mobile	e App (iOS/Android)	
Mobile Scanning	AirPrint®, Mopria®; Optional: Xerox® Workplace Mobile App (iOS/Android)			
Mobile Apps and Xerox® App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize print, convert, route, collaborate and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions).			
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud-based version (Workplace Cloud) of this solution.			

Scan	
Standard Features	Destinations: Scan to USB/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: Scan Preview, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password Protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support
Optional Features	Scan to Cloud Repositories (Dropbox, One Drive and Google Drive) ³ . Xerox [®] Scanning App for DocuShare [®] , other solutions available through various Xerox Business Innovation Partners at xerox.com/Software-Solutions , Print from and Scan to Xerox [®] DocuShare [®] Go content management
Fax	
Standard Features	Internet Fax, Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
Standard Features	802.1x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee® Embedded Control Whitelisting, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager³, LogRhythm SIEM³, Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS 1.1/1.2/1.3, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication (Internal Database), FIPS 140-2. User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot, Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Firmware Verification, Job Level Encryption via HTTPS and Drivers, Signed Email Under evaluation for Common Criteria Certification (ISO 15408), Encrypted Secure Print
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET) ⁴ , Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with Image Overwrite, Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of two-sided documents with up to 270 impressions per minute (ipm).



USER INTERFACE



Intuitive Tablet-like 10.1-inch Color Touchscreen is customizable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

Xerox® Integrated RFID Card

90 access cards.

with the MFP.

Reader (optional) adds card-based authentication with support for over

Near Field Communication (NFC)

Tap-to-Pair allows users to tap their mobile devices to the AltaLink® B8100 Series user panel and quickly connect

Smart Proximity Sensor detects

when users are nearby. It conserves

energy during inactive periods and automatically activates the device when a user approaches.

INNOVATIVE TECHNOLOGIES

PAPER INPUT⁵

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.




Envelope Kit (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 3.5 x 3.9 to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm.



to 6,140 sheets.





Office Finisher (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, making it capable of 60-page booklets

(2 to 15 sheets).



Business Ready (BR) Finisher (optional) gives you advanced finishing functions at a great value.



C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).

LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 12.6 x 52 in./ 320 x 1,320 mm media.





Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with B8145/B8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 50 sheets of 20 lb./75 gsm media.

Device Specification			
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic		
Accessories			
Optional	Finisher Convenience Stapler (includes Work Surface ⁶) Integrated Office Finisher (Available with AltaLink [®] I Office Finisher Booklet Maker for Office Finisher Hole Punch (2/3, 2/4, Swedish) Office Finisher Smart Card Enablement Kit ⁶ Walk-up Fax (One- or Two-line options, includes LAN Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Bluetooth Kit McAfee [®] Integrity Control Enablement Kit USB Keyboard/Shelf Kit Xerox [®] Integrated RFID Card Reader Kit Unicode Font Kit	port Kit) C-fold/Z-fold Unit for BR Finisher or BR Bookk	
Electrical Requirements	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A		Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3%, 10 A		Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A

Device Specification (continued)				
Power Consumption	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Running (Average)	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts	
Standby Mode	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts	
Auto Off/Sleep Mode	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)	
Warm-up (from Off)	As fast as 85 seconds			
Recovery from Sleep	As fast as 4.5 seconds			
Operating Environment				
Required Temperature Range	50 to 82° F/10 to 28° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating: 63.7/64.2 dB(A) Operating: 65.2/67.3 dB(A) Operating: 70.4 dB(A) Standby: 4.0/4.0 dB(A) Standby: 4.3/4.3 dB(A) Standby: 4.3 dB(A)			
Dimensions and Weight				
Base Configuration	Depth: 28.5 in./723 mm Depth: 31.2 in./7 Height: 44.5 in./1,130 mm Height: 46 in./1,		Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 319.2 lb./144.8 kg	
With Office Finisher (with Booklet Mαker)	Width: 47.5 in./1,207 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 370.3 lb./168 kg Weight: 406 lb./184.2 kg		Depth: 31.2 in./793 mm Height: 46 in./1,169 mm	
Base Configuration with Business Ready (BR) Finisher	Width: 55 in./1,395 mm Depth: 28.5 in./723 mm Depth: 31.2 in./723 mm Height: 44.5 in./1,130 mm Weight: 382.3 lb./173.4 kg Weight: 415.4 lb./188.4 kg			
Base Configuration with BR Booklet Maker Finisher	Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 419.7 lb./190.4 kg Weight: 49.3.3 lb./205.6 kg			
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 64.3 in./1,632 mm Width: 64.3 in./1,632 mm Depth: 28.5 in./723 mm Depth: 31.2 in./723 mm Height: 44.5 in./1,130 mm Height: 46 in./1,169 mm Weight: 530.6 lb./240.7 kg Weight: 564.2 lb./255.9 kg			
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit and High Capacity Feeder	Width: 93 in./2,361 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 598.8 lb./271.6 kg		Width: 93 in./2,361 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 632.8 lb./287 kg	
System Certifications/Regulatory Compliance				
Certifications	To view the latest list of certifications, go to xero :	x.com/OfficeCertifications		

Paper Handling	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Single-Pass Duplex Automat	ic Document Feeder (DADF)		
Capacity ⁵	130 sheets		250 sheets
Speed (Up to)	82 ppm black-and-white (simplex) 141 ipm black-and-white (duplex)		135 ppm black-and-white (simplex) 270 ipm black-and-white (duplex)
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 4:	32 mm	
Weights	16 lb. to 32 lb. bond/60 to 128 gsm		
Bypass Tray (Standard)			
Capacity ⁵	100 sheets		
Sizes	Custom Sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 n	nm to 320 x 1320 mm (SEF); Optional: Long Sheet F	eed Kit (Banner Printing)
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm, Long sh	eets/banners (>19 in./483 mm): 28lb Bond - 120lb I	index/106 - 220 gsm
Mediα Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Preprinted Recycled Transparencies Long Sheets/Banners: Card Stock Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock		
Trays 1 and 2 (Standard)	3 3		
Capacity ⁵	520 sheets each		
Sizes	Tray 1: Custom Sizes: 5.5 x 7.2 in. to 11.7 x 17 in./14 Tray 2: Custom Sizes: 5.5 x 7.2 in. to 12 x 18 in./140		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Mediα Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Gard Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock		

Paper Handling (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
High Capacity Tandem Tray	High Capacity Tandem Tray (Available with all models)				
C αραcity ⁵	Tray 3: 867 sheets Tray 4: 1,133 sheets				
Sizes	8.5 x 11 in./A4, JIS B5, Executive (7.25 x 10.5 in) LEF				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted				
Envelope Tray (Optional - Re	places Tray 1)				
Capacity ⁵	Up to 60 envelopes				
Sizes	#10 Commercial (9.25 x 4.125 in.)/Monarch, DL, C5 Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 n	nm to 162 x 241 mm			
Weights	20 lb. to 24 lb. bond/75 to 90 gsm				
High Capacity Feeder (HCF)	(Optional with all models)				
Capacity ⁵	3,000 sheets				
Sizes	Standard Sizes: 8.5 x 11 in. or 7.25 x 10.5 in./A4 or B	5 LEF			
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Total Capacity					
Device Total Capacity ⁵	High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Capa	city Feeder: 6,140 sheets			

Finishing	AltaLink® B8145 AltaLink® B8155 AltaLink® B8170
Output Trays (Standard) (Du	al Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office Finisher and BR Finishers)
Stacking Tray Capacity ⁵	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face up Tray: Up to 100 sheets
Integrated Office Finisher (C	Optional with AltaLink® B8145/B8155)
Stacking Tray Capacity ⁵	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher (Optional)	
Stacking Tray Capacity ⁵	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Multiposition Stapling	50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Hole Punch (Optionαl)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker for Office Fin	isher (Score/Crease, Saddle-stitch Staple) (Optional)
Top Tray Capacity⁵	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm
Score/Crease	1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm
•	r (Optional) (Requires Horizontal Transport Kit)
Capacity ⁵	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
BR Booklet Maker Finisher (Optional) (Requires Horizontal Transport Kit)
Capacity ⁵	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported

Finishing (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
C-fold/Z-fold Unit (Optional	with BR Finisher and BR Booklet Maker Finisher)	'	·
Types	C-fold, Z-fold and Z-half-fold		
Capacity ⁵	40 sheets		
Sizes	C-fold and Z-fold: Letter – 8.5 x 11 in./A4 SEF only Z-half-fold: Tabloid – 11 x 17 in./A3 only		
Weights	16 lb. to 24 lb. bond/64 to 90 gsm		
Output Trays	Envelope Tray: C-fold, Z-fold and Tri-fold Stacker Tray or Top Tray: Z-half-fold		
Convenience Stapler (Option	ıal - Includes Work Surface ⁶)		
Capacity ⁵	50-sheet stapling 5,000 staples Requires separate power outlet		
Сору	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
First-Copy-Out Time (from platen/warmed up)	As fast as 4.4 seconds	As fast as 3.7 seconds	As fast as 3.2 seconds
Sides (input:output)	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999		
Resolution (max)	Up to 600 x 600 dpi		
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% incremen	ts	
Concurrency	Program-ahead to allow job to be queued while initi	al job is processed (Copy, Print, Fax and Scan)	
Copy Features	Annotation and Bates™ stamping Authentication for Services Auto Paper Select Auto Paper Select Auto Reduction & Enlargement (To fit selected pape Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also Collation Covers (Front only, front and back, back only, printed Dividers (blank) Edge Erase Features Help (Intuitive text and graphic description ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Transparencies	o lets you proof each section or delete last section as t I inside and out: Blank or Printed)	the job is built)

Print	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Resolution (up to)	1200 x 2400 dpi		
Print Features	LAN Fax (requires optional Fax Kit) Layout/Watermark N-up (up to 16 pages per sheet) Booklet Layout Long Sheet/Banner Finishing Fit to New Paper Size Hold All Jobs Paper Selection by Attribute Sampl Saved Job Secure Print with Timed Deletion Special Pages (exception page prog Store and Recall Driver Settings	ution (Standard, Enhanced, High) ier, Print ID in margins on first page only or all pages) e Set gramming: covers, inserts, exception pages) th Smart Settings, Duplex, N-up, Turn-off Banner and	
Print from USB	Allows walk-up printing from Type A Supports direct printing from comp Supported file formats: PDF, JPEG, Color jobs can be printed as black-c	outer viα Type B USB port TIFF, PS, PCL	
Operating Systems	Windows Server 2008 SP2 (32- and Windows Server 2008 R2 (64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2012 (64-bit) Windows Server 2019 (64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora Core Ubuntu®	•	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Print Microsoft Windows Networking ove Bonjour®/AirPrint® IPv6 Most protocols not in use can be di), IPv4/IPv6, WSD
Font Capability	PCL: 93 scalable fonts, line printer o	and bitmap font (including Cyrillic font support) PostS	cript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Globαl Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management.		
Xerox® Pull Print Driver	driver. The Xerox® Pull Print Driver e		ngle driver in a Pull Print environment. Uses a single queue and single assets. IT administrators no longer need to manage and configure others.
Unified Address Book for Fax	, Internet Fax, Email and Scan to		
Features	Services supported: Fax, Internet For Maximum contacts: 5,000 Contacts: Supports 1 or more destin Favorites for quick access of all serv	nations	

Scan	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Concurrency	Scan while the system is printing, concurrent jobs)	copying, or while it is transferring scan to network o	fax jobs (priority is for return of scanned originals and printing
Input Speed (up to)	82 ppm black-and-white and colo 141 ipm black-and-white and colo		135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)
Resolution	72 x 72 dpi to 600 x 600 dpi		
Bit Depth	1-bit (black-and-white), 8-bit (gray	yscale), 24-bit (color)	
Maximum Scan Area	11 x 17 in./A3		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS sco	an templates and share via device cloning to other n	nultifunction printers' confirmation sheet options
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS		
File Compression		MMR compression – single or multiple pages)	BIG Arithmetic Compression, Deflate (for black-and-white and within
Document Management Fields (Metadata)		idata fields per network scan to file templates and u name, default value and other configurations	nlimited fields within the template –
Scan Features	Mixed Size Originals Scan Build Job Scan Preview Compression Quality/File Size Cor Original Type (Photo and Text, Ph Auto Background and Shadow Su Size for Size (for mixed size origina TWAIN Support/WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to	oto, Text, Map, Newspaper/Magazine) ppression als)	
Scan to Email (Standard)			
Scan Features	Email signatures (6 lines each of Scan to Email S/MIME Encryptic Email signing (requires Smart Co Auto send to self	on	nfigurable), email Embedded Web Server confirmation sheet options
Directory Access	Address list via LDAP (Windows Ad	ctive Directory, Exchange, Notes, Domino), Device A	ddress Book
Scan To			
Standard Features	Scan to USB Scan to Network Folder (using Sec Scan to Home Scan to Network (using Secure FT Scan to Email Scan to PC/Server Client (SMB or I Scan to Mailbox	P/HTTP/HTTPS)	
Optional Features	Scan to Cloud Repositories (Dropb	pox, One Drive and Google Drive) ³	
Workflow Scanning (Options	ıl)		
Scanning Software	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2		
Scanning Apps and Xerox App Gallery		rive, Microsoft OneDrive®, Microsoft Office 365™, Bo n the Xerox App Gallery: xerox.com/AppGallery	x®, Xerox® Workplace Mobile App (iOS/Android)

Security	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Security Features	AltaLink® B8145 Expanded Authentication Network authentication to access device and/Windows server 2012), NDS, LDAP authentication Local Authentication (internal database) Smart Card authentication — 144k CAC/PIV Co. Secure Data Digitally signed PDF (when using Smart Card of Encrypted and authentication to SMTP server Encrypted/Password Protected PDF (when using Secure Print (up to 10 digit PIN or Network Au. Immediate Image Overwrite/Securely delete ju. On Demand Image Overwrite (Scheduled, Ma. FIPS 140-2 256 bit Hard Disk Encryption, TLS, Expanded Authorization SA access based on network credentials Authorization per user per service User Permissions required to access Print and Foscure Network Access Configuration Watchdog (Monitor and remediated Front USB Port 2 Rear USB Port 2 Rear USB Port 2 Rear USB Port 2 Password Reset Access Control 802.1x Email Alerts - Group 1, 2 and 3 addresses, enally Hold all jobs Reprint Saved Jobs Scan to Mailbox enablement Fax Passcode length System timeout Show/Hide Login Name PostScript® Passwords Remote Services Setup Supplies/Consumables Remot	or device services via Kerberos (UNIX/Window tion ard Support (2048 bit certificate key)/.NET authentication) for Scan to Email ag Email and Network Scan Templates only) thentication) obs using approved algorithms ¹¹ nual), includes sanitation of unused area of di IPPS, HTTPS, SFTP, SNMPv3 Print Features (e.g., time restrictions) reflects in the 29 security settings): Delement, Recipient Group Preferences Enablement Software Download Feature Activation Update Device Settings Daily Synchronization Time Automatically Send Diagnostic Information e/Disable vices unction printers Accounting Reports Succounting Reports	rs Server 2008), SMB (Windows Server 2008,
	Cisco® Identity Services Engine (ISE) compatible Security Information and Event Management (S Full System Common Criteria certified by NIAP u	IEM) support for McAfee® Enterprise Security	
Xerox® Integrated RFID Card Reader (Optional kit)	Integrated support for most industry security card the multifunction printer panel		

Fax	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Network Server Fax Features				
Compatibility				
Maximum Scan Area	11 x 17 in /A3			
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Origin	nal Type (photo, text or photo and text)		
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print			
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi			
Internet Fax Features				
Compatibility	Direct print-ready document transmission to remote Reception and automatic printout of documents ser	Internet Fax machines or email clients (SMTP) nt via email from remote Internet Fax machines or en	nail clients	
Directory Access	Utilizes the Unified Address Book			
Send/Receive	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN,	JPEG		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)			
Network Protocols	SMTP (send), POP3 (receive)			
Compliance	ITU-T T.37 compliant			
Walk-up Fax Features (Option	nal; Customer-Installable – 1 and 2 lines)			
Compatibility	ITU (CCITT) Group 3			
Speed/Modems	One or Two V.34 modems: 33,600 bps. Less than 4 s	econds per page transmission time		
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3			
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes			
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 5,000 contacts)			
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, he Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay	ader)/Auto		
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only			
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report			
Directory Access	Utilizes the Unified Address Book Group fax available			
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals			
Auto Resend	Up to 5 attempts			

Device Management	
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Configuration Orchestrator, Configuration Watchdog
Xerox® CentreWαre® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer • Remote configuration of SNMP v3 • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Requires Windows 7 and Internet Explorer 6.0 and higher • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions
Xerox® Device Types for SAP R/3 Intelligent Bar- code Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® Multifunction Printers by storing Xerox® Software, as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at office.xerox.com/Software-Solutions
Xerox [®] Embedded Web Serve	er – Integrated Device Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	
	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator
Browsers	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x
Browsers Support	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x
	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x
Support	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x Install print/scan drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish,
Support Languages Supported Remote Services Xerox® Automatic Meter Readings (AMR)	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x Install print/scan drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Support Languages Supported Remote Services Xerox® Automatic Meter Readings (AMR) Xerox® Automatic Supplies Replenishment (ASR)	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x Install print/scan drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming
Support Languages Supported Remote Services Xerox® Automatic Meter Readings (AMR) Xerox® Automatic Supplies	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x Install print/scan drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Support Languages Supported Remote Services Xerox® Automatic Meter Readings (AMR) Xerox® Automatic Supplies Replenishment (ASR) Accounting	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x Install print/scan drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Support Languages Supported Remote Services Xerox® Automatic Meter Readings (AMR) Xerox® Automatic Supplies Replenishment (ASR) Accounting Xerox® Standard Accounting	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x Install print/scan drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory. (Standard)

Accounting Options – Network Accounting (Allows central server to manage all accounting) • Enhanced network accounting with up-to-the-minute data on how the system is being used • Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support $\bullet \ \, \text{Device requests account authentication from third-party server enabling larger databases of users and accounts}$ • Accept Authentication Login at control panel and pass to third-party Networking Account • Interface with third-party accounting terminal for accounting user interface **Supplies** Description Yield Toner Cartridge Black 52,000 pages Transfer Belt Cleaner 1 Assembly 160,000 pages Second Bias Transfer Roll 200,000 pages 1 Assembly Staple Cartridges For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton) 5,000 each cartridge For BR Booklet Maker (1 cartridge per carton) 5,000 each cartridge For Office Finisher Booklet Maker (8 cartridges per carton) 2,000 each cartridge For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton) Staple Refills 5,000 each refill Xerox® Smart Kit® Drum Cartridge9 1 Cartridge 200,000 pages **Waste Toner Container** 1 Cartridge (AltaLink® B8145/8155) 121,000 pages w/o Suction Filter1 **Waste Toner Container** 1 Cartridge (AltaLink® B8170) 121,000 pages with Suction Filter¹⁰

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office



Declared in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis

³ Available post-launch via software update.

⁴Not available in all geographies.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁶ Sold separately in some geographies

Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points.

⁸ Under evaluation; certification expected in Q2 2021.

⁹Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with split of 35% color/65% black-and-white pages.

 $^{^{10}\,\}text{Waste}$ Toner Container yield will vary depending on type of image, area coverage $\,\%\,$ and Job run length.

¹¹ With optional Hard drive.